

US08762A

[11] Patent Number: 5,538,762
[45] Date of Patent: Jul. 23, 1996

4,961,996 10/1990 Carr et al. 428/421

FOREIGN PATENT DOCUMENTS

363924 11/1989 European Pat. Off.
367438 5/1990 European Pat. Off.
386784 9/1990 European Pat. Off.

OTHER PUBLICATIONS

Abstract of JP 61-016910, Jan. 1986.
World Patents Index Latest, Derwent Publications Ltd.,
London, GB: AN 86-065417 & JP-A-61 016 910 (Hitachi
Cable KK), Jan. 24, 1986 (abstract).

Primary Examiner—Shirley Beck
Assistant Examiner—Emma Cameron
Attorney, Agent, or Firm—Fish & Richardson

[57] ABSTRACT

A method of contacting a substrate having a surface containing hydroxyl groups with a non-aqueous solution containing a material having a chrollosilyl group; washing if desired; coating the substrate with a non-aqueous solvent containing a compound having a fluorocarbon group and a chlorosilane group or a solvent containing a compound containing a fluorocarbon group and an alkoxy silane; and baking the substrate if necessary in order to form a fluorocarbon-based polymer coating film chemically bonded to the substrate surface. The hydroxyl groups on the substrate surface and chlorosilyl groups are reacted to form a thin film having a large number of silanol groups (—SiOH) capable of connecting the polymer coating film to the substrate to form a heat-, weather-, and wear-resistant film on various surfaces.

11 Claims, 6 Drawing Sheets